

SSY-B尺寸表

导体标准	公差	标准外径	绕组线最大	导体电阻	重量
直径(mm)	±(mm)	(mm)	外径(mm)	Ω /m	kg/ km
0.200	0.008	0.400	0.417	607.600	0.398
0.210	0.008	0.410	0.427	549.000	0.431
0.220	0.008	0.420	0.437	498.400	0.465
0.230	0.008	0.430	0.447	545.500	0.500
0.240	0.008	0.440	0.457	416.200	0.537
0.250	0.008	0.450	0.467	382.500	0.575
0.260	0.010	0.460	0.477	358.400	0.616
0.270	0.010	0.470	0.487	331.400	0.656
0.280	0.010	0.480	0.497	307.300	0.697
0.290	0.010	0.490	0.507	285.700	0.742
0.300	0.010	0.500	0.520	262.900	0.786
0.320	0.010	0.520	0.540	230.000	0.882
0.350	0.010	0.550	0.570	191.200	1.033
0.370	0.010	0.570	0.590	170.600	1.143
0.400	0.010	0.600	0.625	145.300	1.316
0.450	0.010	0.650	0.675	114.200	1.633
0.500	0.010	0.700	0.725	91.430	1.985
0.550	0.020	0.750	0.775	78.150	2.371
0.600	0.020	0.800	0.825	65.260	2.793
0.650	0.020	0.850	0.875	55.310	3.249
0.700	0.020	0.900	0.925	47.470	3.741
0.750	0.020	0.950	0.975	41.190	4.267
0.800	0.020	1.000	1.030	36.080	4.829
0.850	0.020	1.050	1.080	31.870	5.425
0.900	0.020	1.100	1.130	28.350	6.056
0.950	0.020	1.150	1.180	25.380	6.721
1.000	0.030	1.200	1.230	23.330	7.422